

# EL-WiFi-DTP+

High Accuracy Dual Channel

Thermistor Probe WiFi Temperature Data Logger



- **Dual channel recording through two external thermistor probes**
- **Wirelessly stream and view data using the EasyLogCloud or on a PC**
- **Data Logger set up is easy using our free PC software**
- **View and analyse multiple loggers, including graphing of historic data**
- **Measures temperature range -40°C to +125°C (-40°F to +257°F)**
- **Configurable high and low alarms with indicator**
- **Logger memory stores data even if WiFi is temporarily disconnected**

The EL-WiFi-DTP+ data logger measures the temperature of the environment in which the two probes are situated. This high accuracy sensor is typically accurate to  $\pm 0.2^{\circ}\text{C}$  ( $-15^{\circ}\text{C}$  to  $+80^{\circ}\text{C}$ ). The unit is freestanding, but can be attached to a wall or surface using the bracket provided. The unit can be clipped in and out of the bracket as required. The probes are connected to the sensor via a 160mm Y splitter cable which is provided.

Data is streamed wirelessly to a local PC or to our Cloud service. During configuration, the data logger will search for an existing wireless network whilst physically connected to the PC. It can then be placed anywhere within range of the network. If the data logger temporarily loses connectivity with the network, it will log readings until the connection is re-established (max 30 days at 10 second sample interval).

Although EasyLog WiFi data loggers have an impressive range this can be increased by using WiFi extenders which are available from [www.lascarelectronics.com](http://www.lascarelectronics.com).

The EL-WiFi-DTP+ is a low power device containing a rechargeable battery. When configured using typical sample and transmit periods the data logger can operate for up to six months. The battery can be recharged via a standard +5V wall adapter or a USB port using the cable provided.

The LCD display includes several features including Max and Min readings and indicators for battery state, alarms, WiFi connection and signal strength.

With our free PC software you can choose to store your data either locally on a single PC, or make it universally accessible on the Cloud. Whichever you choose, you'll be able to analyse data, draw graphs and export the latest and historic data in various formats.

You can change the data logger's settings to suit your needs, options include:

- Assigning names to the logger and each measuring channel
- Selecting the units of measurement
- Choosing the sample rate and transmission period
- Setting high and low alarm levels for each channel

Once configured, data logger settings can be changed remotely, without the need to reconnect it to your PC.

The EL-WiFi-DTP+ has a protection rating of IP43 and the probes IP67. The data logger is IEEE 802.11b compliant, supports WEP, WPA/WPA2 encryption and enterprise networks\*.

A range of recommended accessories, including ADSL routers, USB mains chargers and spare probes are available from [www.lascarelectronics.com](http://www.lascarelectronics.com).

\*MS-CHAPv2, PEAP, EAP-FAST, EAP-TTLS

# EL-WiFi-DTP+

High Accuracy Dual Channel

Thermistor Probe WiFi Temperature Data Logger



Specifications	Minimum	Typical	Maximum	Unit
Battery life		>6*		Months
USB supply voltage	4.5		5.5	Vd.c.
Operating temperature range	-20 (-4)		+60 (+140)	°C (°F)
Logging period (user configurable)	10 sec	10 min	12 hrs	
Transmission period (user configurable)	1 min	1 hr	24 hrs	
Temperature measurement range	-40 (-40)		+125 (+257)	°C (°F)
Temperature measurement resolution		0.01		°C
Temperature display resolution		0.01		°C
Temperature accuracy		±0.2°C (-15 to +80°C)	±0.6°C (-40 to +125°C)	°C

*Warning - do not exceed operating temperatures*

## Battery Life and Power Supply

The product will arrive partly charged but ideally you should charge it for 24 hours before use for optimum performance. The battery can be recharged (unit must be between 0 - 40 °C) via a PC, a USB +5V wall adapter, or a portable USB battery pack using the cable provided. It can also be permanently powered by a USB wall adapter or USB battery pack.

\*Battery life is dependent on: transmission period, WiFi encryption method, WiFi encryption key rotation frequency (determined by the router/access point), signal strength between router/access point and WiFi device, presence volume and type of WiFi traffic from other devices, sample rate and operating temperature.

*We're committed to continuously improving our products. Specifications are liable to change without warning.*