


Electrocorder

Model:
EC-3V



- 3Ø
- 500V
- 3V
- USB
- IP65

Three phase 500Vac

Integral phase sequence or rotation checker

Complete with Electrosoft energy analysis software

Sealed to IP65/NEMA 12/4

Allows engineers to quickly and cost effectively monitor & resolve single & 3-phase voltage problems.


Data stored in non-volatile memory.

Memory capacity of 32,000 (True RMS) values per channel (10bit), up to 300 days continuous recording.

Selectable averaging period from 1 second to 60 minutes.

Voltage accurate to $\pm 1\%$ of reading, ± 1 volt.

Kit includes data logger, voltage input leads, USB lead, Electrosoft software and a carry case.



The advantage of ElectroCorder products over most others is that our Data Loggers constantly sample information (recording the Minimum, Maximum and Average reading) over the set period. Many other products only take 'snap shots' of what is going on and can miss 99.9% of the data that is critical to your analysis.

The EC-3V is designed to allow electrical engineers to cost effectively monitor single and three phase supplies. Our products allow voltage problems to be highlighted quickly and investigated.

Setting up the Electrorecorder EC-3V is easy, suitable for non-technical staff. Using the supplied (free) Windows software, Electrosoft, input the location details for the logging and choose the logging period. Electrosoft will print the necessary dispatch/return documentation including user instructions. All data is included in a database of dispatches and returns, allowing you to track the location of multiple loggers.

Why is the Electrorecorder better than other similarly priced competitors? The Electrorecorder range uses a constant sampling technique, unlike the single reading of competitors. When the loggers start to record, they sample every channel 16 times per cycle, a cycle is 16ms at 60Hz. At the end of each averaging period, 3 quantities are saved for each channel: the True RMS average, the Max, which is the highest cycle value during the period and the Min, the lowest cycle value. This means that it will record all the peaks and troughs which are one cycle or longer.

Technical specifications (subject to change without notice)

Measurement Range	0Vac to 500Vrms (Ph - Ph) or 0V to 300Vrms (Ph - N)
Maximum Channel Input Voltage	500Vrms (Ph - Ph), 300Vrms (Ph - N) or 700/peak
V _{min} & V _{max} Measurement Time Resolution	Always one cycle (60Hz), independent of selected averaging period
Inputs (Non-Isolated Inputs)	Three phase inputs (L1, L2 & L3) & Neutral (N), Non-isolated input channels
Input Socket Types	4mm shrouded 'banana' plugs & sockets, each with insulated crocodile clip
Measurement Accuracy	±1% of reading ± 1 Volt, 90Vac - 450 Vrms (Ph - Ph); else ±3% (60Hz ±2%)
Sampling Frequency	16 samples per cycle 960Hz @ 60Hz
Data Recorded	Average voltage, max & min voltage-cycle-value during the averaging period
Memory Capacity	192kB able to record 32,000 levels per phase
Memory Type	Non-volatile SEEPR0M
Memory - Averaging Period & Duration	1 sec to 60 mins (1sec gives 2 hrs logging, 60 min gives 300 days logging)
Real-Time Clock Accuracy	Greater than 0.001%
Input Lead Length	6' 6" (6 feet, 6 inches)
Battery Life (While Plugged In)	Unlimited - mains powered & battery backup (9,000 hours, 1 year while unpowered)
Battery Type	Unit contains fourteen 9V alkaline batteries (E-Block, PP3, 1604A)
Communications Interface Type	USB, optically isolated to 5,2kV
Electrosoft Software	Windows (9x, 2k, ME, NT, XP, Vista & Windows 7); 1024 x 769 min resolution
Environmental (Temp & Sealing)	-10C to +40C or +14°F to +104°F, Sealed to IP65
Dimensions & Weight	10" x 6" x 3" & 1lb

The voltage levels are stored with dates and times. With the back-up battery, the Electrorecorder can continue to record for up to a year.

The recorded data is uploaded to a PC via the supplied USB cable. Using Electrosoft, the recorded voltage levels with dates and times can be viewed in both tabular and graphical form, exported to a spreadsheet or saved to file. Graphs can be printed showing the recorded levels and the allowable tolerance bands. These results may then be discussed with the customer.

On the logger, recording is signified by a flashing green light. A red light advises users that the unit has completed recording.

Warranty & Calibration

All Accsense Electrorecorder products carry a *Lifetime back to base warranty covering manufacturing defects and component failures. Each unit is individually calibrated during testing.

*Refer to website for full terms and conditions.

Conformity

Emissions EN55022:1994B, (EN50081-1:1992). Immunity EN50082-2:1995, following the provisions of EMC directive 89/336/EEC. Recording std EN50160:1994. LVD 72/23/EEC with respect to EN60065. (IEC-61010). All models certified (light industrial, 3V/m).